


## RISE 4260HD Series with Command Core™

H.264 High-Definition, IP68 Camera Positioning System

Lifetime Warranty on Camera Head Moisture Ingress



FDOT APL Approved



### Advanced Optics

- Superior 1080p image quality
- Powerful 30x optical + 12x digital zoom (360x total)
- Image defog/dehaze analytics
- Electronic image stabilization (EIS)
- Dark scene enhanced intensity
- Bright source whiteout reduction
- Presets, tours, sectors and privacy zones

### Rugged Construction

- Operates in hurricane force winds
- Built-in electrical transient/surge protection to CISPR 24 levels
- Precision positioning of 0.05°
- Pressurized IP68 Camera Head
- NEMA TS2 temperature -40°C to 75°C
- Processor controlled heated faceplate
- Integrated faceplate wiper option
- Inverted mounting capability
- Three Year Standard Warranty
- 3 Year Standard Warranty, Lifetime Warranty on moisture ingress into camera head enclosures.

### Installation and Interoperability

- ONVIF Profile S and NTCIP 1205 compliant
- 5 individually onfigurable video streams
- Hybrid IP/analog video-serial PTZ operation
- H.264 Base/Main/High profiles and MJPEG
- Web configuration, operation and viewing
- Inverted mounting capability
- Single CAT5e cable with PoE++
- Pendent, wall, pole and corner mounting bracket options
- Built-In Setup Configuration wizards

### Command Core™ Action Engine

- Automated camera responses
- Preset/Tour activations
- Digital I/O triggers and actions
- Image snapshots with FTP/EMAIL delivery
- Built-in Configuration Wizards
- Three trigger queuing modes

### OptiCore™ Management

- Free Camera Management Tool
- Camera Configuration
- Automated Updates

## RISE 4290HD Series with Command Core™

H.264 Dual Spectrum Night-Vision Positioning System

Lifetime Warranty on Camera Head Moisture Ingress



FDOT APL Approved



### Advanced Optics

- Superior 1080p image quality
- Powerful 30x optical + 12x digital zoom (360x total)
- Image defog/dehaze analytics
- Electronic image stabilization (EIS)
- Dark scene enhanced intensity
- Bright source whiteout reduction
- Presets, tours, sectors and privacy zones

### Rugged Construction

- Operates in hurricane force winds
- Built-in electrical transient/surge protection to CISPR 24 levels
- Precision positioning of 0.05°
- Pressurized IP68 Camera Head
- NEMA TS2 temperature -40°C to 75°C
- Processor controlled heated faceplate
- Integrated faceplate wiper standard
- Inverted mounting capability
- 3 Year Standard Warranty, Lifetime Warranty on moisture ingress into camera head enclosures.

### Advanced Night Vision Performance

- Night vision LWIR 8-14um spectrum
- VOx uncooled micro bolometer technology
- 640 x 480 resolution, 17um FPA
- Up to 6x Continuous zoom, dual FoV or fixed thermal optics options
- Auto-focus On-Demand (zoom/dual FoV options only)
- Synchronized optical zoom views

### Installation and Interoperability

- ONVIF Profile S and NTCIP 1205
- 5 individually onfigurable video streams
- Hybrid IP/analog video-serial PTZ operation
- H.264 Base/Main/High profiles and MJPEG
- Web configuration, operation and viewing
- Single CAT5e/CAT6 cable with PoE++
- Pendent, wall, pole mounting options
- Built-In Setup Configuration wizards

### OptiCore™ Management

- Free Camera Management Tool
- Camera Configuration
- Automated Updates



youtube.com/CohuHD  
 linkedin.com/company/CohuHD  
 twitter.com/CohuHD  
 facebook.com/CohuHD  
 CohuHD.com

## RISE 4220HD Series with Command Core™ H.264 High-Definition, IP68 Dome Positioning System



FDOT APL  
Approved



### Advanced Optics

- Superior 1080p image quality
- Powerful 30x optical + 12x digital zoom (360x total)
- Image defog/dehaze analytics
- Electronic image stabilization (EIS)
- Dark scene enhanced intensity
- Bright source whiteout reduction
- Presets, tours, sectors and privacy zones

### Rugged Construction

- Operates in hurricane force winds
- Built-in electrical transient/surge protection to CISPR 24 levels
- Precision positioning of 0.1°
- Pressurized IP68 Ingress Protection
- NEMA TS2 temperature -40°C to 75°C
- Processor controlled heater
- Three Year Standard Warranty, Lifetime Warranty on moisture ingress into camera head enclosure

### Installation and Interoperability

- ONVIF Profile S and NTCIP 1205 compliant
- H.264 Base/Main/High profiles and MJPEG
- Web configuration, operation and viewing
- Single CAT5e/CAT6 cable with PoE++
- Pendant, wall and pole mounting bracket options
- Built-In Setup Configuration wizards


### Command Core™ Action Engine

- Automated camera responses
- Preset/Tour activations
- Digital I/O triggers and actions
- Image snapshots with FTP/EMAIL delivery
- Built-in Configuration Wizards
- Three trigger queuing modes

### OptiCore™ Management

- Free Camera Management Tool
- Camera Configuration
- Automated Updates

## The CoHuHD Costar Difference



youtube.com/CoHuHD  
linkedin.com/company/CoHuHD  
twitter.com/CoHuHD  
facebook.com/CoHuHD  
CoHuHD.com